

Arco PC (Runner)

Art der Herstellung	Tufted	ISO 2424
Teilung	1/8" Cutpile	
Nutzschicht	100% PA6	ISO 2424
Trägermaterial	Non Woven	
Rücken	PC	
Polgewicht	750 g/m ²	
Gesamtgewicht	3460 g/m ²	+/- 10% ISO 8543
Polhöhe	5,5 mm	ISO 1765
Gesamthöhe	8,0 mm	+/- 10% ISO 1765
Noppenzahl	132300	
Beanspruchungsbereich	Commercial 32, Areas with medium use	EN 1307
Komfortklasse	LC3	EN 1307
Stuhlrolleneignung	Yes, incidental use	EN 985
Treppeneignung	Yes, permanent use	EN 1307
Lichtechtheit	≥ 5	ISO 105-B02
Reibechtheit, trocken & nass	≥ 4	ISO 105-X12
Wasserechtheit	≥ 4	ISO 105-E01
Apparative Anschmutzung	≥ 3,5	EN 1269
Gleitwiderstand	> 0,3 Machine direction > 0,3 Crossdirection	EN 13893 EN 13893
Brandverhalten	Cfl,s1	EN 13501-1
Prodis-ID (GuT)	D3F1CA7E	www.pro-dis.info
AbZ Nr.	Z-156.601-1165	

Floorsymbols



Certificates

Vebe PA6 / 1145 / PVC



EN 14041



Reaction to fire:
Cfl,s1

Slip resistance:
DS

DOP:
1061#606PC00
Textile Floorcovering
EN1307



Vebe Floorcoverings b.v. certifies the supplied products to meet the requirements as specified and stated in the last editions of the technical information. The products have been produced and tested according procedures agreed in our quality system (according ISO 9001). The tests have been carried out according to the prescribed standards.