

Almera PC (Runner)

Art der Herstellung	Tufted	ISO 2424
Teilung	1/8" Cutpile	
Nutzschicht	100% PA6	ISO 2424
Trägermaterial	Non Woven	
Rücken	PC	
Polgewicht	840 g/m ²	
Gesamtgewicht	3410 g/m ²	+/- 10% ISO 8543
Polhöhe	3,8 mm	ISO 1765
Gesamthöhe	7,0 mm	+/- 10% ISO 1765
Noppenzahl	88200	
Beanspruchungsbereich	Commercial 32, Areas with medium use	EN 1307
Komfortklasse	LC2	EN 1307
Stuhlleneignung	No	EN 985
Treppeneignung	Yes, permanent use	EN 1307
Lichtechtheit	≥ 5	ISO 105-B02
Reibechtheit, trocken & nass	≥ 4	ISO 105-X12
Wasserechtheit	≥ 4	ISO 105-E01
Apparative Anschmutzung	≥ 3,5	EN 1269
Gleitwiderstand	> 0,3 Machine direction	EN 13893
	> 0,3 Crossdirection	EN 13893
Brandverhalten	Cfl,s1	EN 13501-1
AbZ Nr.	Z-156.601-1165	

Floorsymbols



Certificates

Vebe PA6 / 1145 / PVC



Emissionsgeprüfter Bodenbelag nach DIBt-Grundsätzen

EN 14041



Reaction to fire:
Cfl,s1

Slip resistance:
DS

DOP:
1061#61PPC00
Textile Floorcovering
EN1307

Vebe Floorcoverings b.v. certifies the supplied products to meet the requirements as specified and stated in the last editions of the technical information. The products have been produced and tested according procedures agreed in our quality system (according ISO 9001). The tests have been carried out according to the prescribed standards.